VOLUFIX/ VOLUMETRIC SET MEASURED VOLUME SET



Volufix® SS-3082

- Burette type chamber of **100 ml capacity with 10 ml overflow limit.**
- Micro drip with drop size of **60 drops/ml.**
- Soft and flexible burette chamber.
- Hanger enables hanging to the I.V stand.
- **Floating auto shut-off valve** acts as floating/ volume indicator and automatically shuts off the drain path to **prevent air embolism.**
- Patented design, no-kink device prevents kinking of tube during transit.
- Flash **ball type injection site** for extra medication.
- Roller type flow controller provides precise flow control.
- Sterile, disposable, non-pyrogenic, individually packed.
- Box of 10/ Master Box of 100.

SPECIFICATIONS

Capacity	Drop Rate
110 ml	60 drops/ml

Volumetric® Set SS-3094

- Large calibrated burette chamber.
- Measured volume set with **burette chamber of 150 ml.**
- Soft and flexible burette chamber suitable for most of the prescribed fluids.
- Sharp piercing spike provided with built in air inlet with bacterial barrier filter.
- Micro drip with reduced drop size of **60 drops/ml.**
- Hanger enables hanging to the I.V stand.
- Floating auto shut-off valve acts as volume indicator and automatically shuts off the path to prevent air embolism.
- Patented design, no-kink device prevents kinking of tube.
- Flash **ball type injection site** and needle.
- Sterile, disposable, non-pyrogenic, individually packed.
- Box of 10/ Master Box of 100.

SPECIFICATIONS

Capacity	Drop Rate
150 ml	60 drops/ml

BI-VALVE THREE WAY STOP COCK



Bi-Valve® GS-3040 L

- Specially designed **lipid resistant 3-way stop cock** with smooth tap rotation suitable during pressure infusion and invasive blood pressure monitoring.
- Made from clear, transparent polycarbonate which facilitates **easy visualization of fluid flow.**
- Rigid construction with circular flow channel **prevents air entrapment.**
- Smooth three arm handle is easy to operate and indicates fluid path.
- Minimum residual volume and **uniform bore** ensures maximum flow and minimum turbulence.
- Provided with two female luer lock ports and one male luer lock port.
- Male luer lock with rotating nut prevents accidental disconnection.
- **Screw luer lock** ensures safe and secure connection to other standard luers.
- **Universal luer taper** facilitates leak proof connection.
- Sterile, individually packed in blister pack.
- Box of 50/ Master Box of 1000.

SPECIFICATIONS

Residual Vol.	Pressure
≤ 0.20 ml	5 bar

SPECIAL FEATURES

★ Lipid compatible ★ Minimum prime volume
★ Arrows indicate flow direction ★ Leakage free fitment